



## Zebra ZD421d - Label printer - direct thermal

Roll (10.8cm) - 203 dpi - up to 152 mm/sec - USB 2.0 - LAN - USB host - grey

|                       |                  |
|-----------------------|------------------|
| Group                 | Printers         |
| Manufacturer          | Zebra            |
| Manufacturer item no. | ZD4A042-D0EE00EZ |

### Description

The ZD421 builds on the legacy of Zebra's GK Series printers, offering you the functions and capabilities of its predecessor - and much more. The next-generation ZD421 leverages this heritage to deliver advanced features for a new era of intelligence and forward flexibility.

### Main features

|                              |  |
|------------------------------|--|
| Product Description          | Zebra ZD421d - label printer - B/W - direct thermal  |
| Printer Type                 | Label printer - direct thermal - B/W   |
| Weight                       | 1.35 kg  |
| Localisation                 | United Kingdom, Europe   |
| Max Media Size               | Roll (10.8cm)  |
| Min Media Size (Custom)      | 15 mm  |
| Max Media Size (Custom)      | 108 mm x 991 mm  |
| Print Speed                  | Up to 152 mm/sec - max speed   |
| Max Resolution (B&W)         | 203 dpi  |
| Interface                    | USB 2.0, LAN, USB host   |
| RAM Installed (Max)          | 256 MB SDRAM   |
| Flash Memory Installed (Max) | 512 MB   |
| Language Simulation          | ZPL II, EPL2, ZBI, Extensible Mark-up Language (XML), PDF Direct   |
| Barcodes                     | Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, Plessey, Standard 2 of 5, EAN-8, EAN-13, MSI |
| Media Type                   | Receipt paper, tag stock, continuous labels, die cut labels, wristband labels, fanfold labels  |
| Features                     | Realtime clock, Print Touch tag, transmissive/gap sensor, reflective/black mark sensor   |
| Networking                   | Print server   |
| Power                        | AC 120/230 V   |
| Enclosure Colour             | Grey   |

Dimensions (WxDxH) 17.75 cm x 22.08 cm x 15.07 cm

## Extended details

| <b>General</b>                  |  |
|---------------------------------|--|
| Printer Type                    | Label printer - direct thermal - monochrome  |
| Enclosure Colour                | Grey   |
| Localisation                    | United Kingdom, Europe   |
| <b>Printer</b>                  |  |
| Print Speed                     | Up to 152 mm/sec - max speed   |
| Connectivity Technology         | Wired  |
| Interface                       | USB 2.0, LAN, USB host   |
| Max Resolution (B&W)            | 203 dpi  |
| Language Simulation             | ZPL II, EPL2, ZBI, Extensible Mark-up Language (XML), PDF Direct   |
| Features                        | Realtime clock, Print Touch tag, transmissive/gap sensor, reflective/black mark sensor   |
| Fonts Included                  | 16 x bitmapped ZPL II   2 x scalable ZPL   5 x expandable EPL2   |
| Barcodes                        | Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, Plessey, Standard 2 of 5, EAN-8, EAN-13, MSI |
| <b>RAM</b>                      |  |
| RAM Installed (Max)             | 256 MB   |
| Technology / Form Factor        | SDRAM  |
| <b>Flash Memory</b>             |  |
| Flash Memory                    | 512 MB   |
| <b>Media Handling</b>           |  |
| Media Type                      | Receipt paper, tag stock, continuous labels, die cut labels, wristband labels, fanfold labels  |
| Max Media Size                  | Roll (10.8cm)  |
| Min Media Size (Custom)         | 15 mm  |
| Max Media Size (Custom)         | 108 mm x 991 mm  |
| Media Sizes                     | Roll (1.5 - 10.8 cm)   |
| Max Printing Width              | 104 mm   |
| Media Thickness Range           | 0.08 mm - 0.19 mm  |
| Roll Maximum Outer Diameter     | 127 mm   |
| Roll Core Diameter              | 25.4 mm, 76.2 mm, 38.1 mm, 12.7 mm, 50.8 mm  |
| Media Feeders                   | 1 x manual - 1 roll - Roll (10.8cm)  |
| <b>Networking</b>               |  |
| Networking                      | Print server   |
| <b>Expansion / Connectivity</b> |  |
| Connections                     | 1 x USB 2.0 - 4 pin USB Type B   1 x USB host - 4 pin USB Type A   1 x LAN - RJ-45   |
| <b>Miscellaneous</b>            |  |
| Included Accessories            | 2 core adapters, 2 ribbon cores  |



|                                 |   |
|---------------------------------|---|
| Cables Included                 | 1 x USB cable   |
| Features                        | Printer setup mobile app via BLE connection   |
| Compliant Standards             | FCC Class B certified, VCCI, C-Tick, BSMI, EN 61000-3-2, ICES-003, NOM, SABS, EN 61000-3-3, EN55024, EN55022 Class B, FCC Part 15.247, CCC, IC, IEC 60950-1, KCC, FCC Part 15.209, S Mark, cTUVus, EN 62311, EN 300 328, BIS, INMETRO, CU, RSS-247, IEC 62368-1, EN 301 893, RoHS 2011/65/EU Amendment 2015/863 |
| <b>Power</b>                    |   |
| Power Device                    | Power adapter - external  |
| Voltage Required                | AC 120/230 V  |
| Frequency Required              | 50/60 Hz  |
| Power Factor Correction         | Yes   |
| <b>Environmental Standards</b>  |   |
| ENERGY STAR                     | Yes   |
| <b>Manufacturer Warranty</b>    |   |
| Service & Support               | Limited warranty - 2 years  |
| <b>Environmental Parameters</b> |   |
| Min Operating Temperature       | 4.4 °C  |
| Max Operating Temperature       | 41 °C   |
| Humidity Range Operating        | 10 - 90% (non-condensing)   |
| <b>Dimensions &amp; Weight</b>  |   |
| Width                           | 17.75 cm  |
| Depth                           | 22.08 cm  |
| Height                          | 15.07 cm  |
| Weight                          | 1.35 kg   |

Technical data © CNET Content Solutions. Subject to technical modifications and errors.