

Zebra ZT231 - Label printer - thermal transfer

Roll (11.4 cm) - 203 dpi - up to 305 mm/sec - USB - LAN - serial - Bluetooth

Group	Printers
Manufacturer	Zebra
Manufacturer item no.	ZT23142-T0E000FZ
EAN/UPC	5715063012918



Description

Demands are rising and timelines are shrinking. Do you have the printing capabilities to keep up - without interruption The ZT231 delivers the winning combination of the right features at the right price, along with the long-lasting quality you expect from Zebra. Fast print speeds, high-resolution print quality, large color touchscreen, future-forward design and more - all in one space-saving footprint. Plus, add optional capabilities like RFID, wireless connectivity and media handling features when you need them. But that's not all. Get built-in intelligence to make your work easier, and unmatched security so nothing stands in your way. That's how Zebra defines value.

Main features

Product Description	Zebra ZT231 - label printer - B/W - thermal transfer
Printer Type	Label printer - thermal transfer - B/W
Weight	9.1 kg
Localisation	United Kingdom, Europe
Max Media Size	Roll (11.4 cm)
Min Media Size (Custom)	19.4 mm
Max Media Size (Custom)	114 mm
Print Speed	Up to 305 mm/sec - B/W - Roll (11.4 cm)
Max Resolution (B&W)	203 dpi
Interface	USB, LAN, serial, Bluetooth
RAM Installed (Max)	256 MB SDRAM
Flash Memory Installed (Max)	256 MB
Language Simulation	ZPL, ZPL II, EPL2, EPL
Barcodes	Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, TLC39, Plessey, Code 128B, Code 128C, Code 128A, Standard 2 of 5, MSI, RSS-14
Media Type	Continuous labels, die cut labels, black mark labels, notch
Networking	Print server
Printer Features	Zebra Programming Language (ZPL) support, Multi-level Element Energy Equalizer (E3)
Power	AC 100-240 V

Dimensions (WxDxH) 24.1 cm x 43.2 cm x 27.9 cm

Extended details

General

Printer Type Label printer - thermal transfer - monochrome
Localisation United Kingdom, Europe

Printer

Print Speed Up to 305 mm/sec - B/W - 203 dpi - Roll (11.4 cm)
Built-in Devices 4.3 inch colour LCD touch screen
Connectivity Technology Wireless
Interface USB, LAN, serial, Bluetooth
Max Resolution (B&W) 203 dpi
Language Simulation ZPL, ZPL II, EPL2, EPL
Fonts Included 1 x scalable | 7 x bitmapped
Barcodes Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, TLC39, Plessey, Code 128B, Code 128C, Code 128A, Standard 2 of 5, MSI, RSS-14
Printer Features Zebra Programming Language (ZPL) support, Multi-level Element Energy Equalizer (E3)

RAM

RAM Installed (Max) 256 MB
Technology / Form Factor SDRAM

Flash Memory

Flash Memory 256 MB

Media Handling

Media Type Continuous labels, die cut labels, black mark labels, notch
Max Media Size Roll (11.4 cm)
Min Media Size (Custom) 19.4 mm
Max Media Size (Custom) 114 mm
Media Sizes Roll (1.94 - 11.4 cm)
Max Printing Width 104 mm
Max Printing Length 3988 mm
Media Thickness Range 0.076 mm - 0.25 mm
Roll Maximum Outer Diameter 203 mm
Roll Core Diameter 76 mm, 25 mm
Media Feeders 1 x manual - 1 roll - Roll (11.4 cm)

Networking

Networking Print server

Expansion / Connectivity

Connections 1 x RS-232 - 9 pin D-Sub (DB-9) | 1 x USB 2.0 | 1 x LAN

	Miscellaneous
Compliant Standards	FCC Class B certified, VCCI, BSMI, EN 61000-3-2, ICES-003, EN 61000-3-3, EN55024, EN55022 Class B, FCC Part 15.247, CCC, KCC, FCC Part 15.209, S Mark, cTUVus, EN 62311, RCM, EN 300 328, BIS, RSS-247, IEC 62368-1, EN 301 893, EN 55035, UKCA
	Power
Power Device	Power supply - internal
Voltage Required	AC 100-240 V
Frequency Required	50 - 60 Hz
	Environmental Standards
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 1 year
	Environmental Parameters
Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 85% (non-condensing)
	Dimensions & Weight
Width	24.1 cm
Depth	43.2 cm
Height	27.9 cm
Weight	9.1 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.