

# Zebra ZT400 Series ZT411 - Label printer

direct thermal / thermal transfer - Roll (11.4 cm) - 203 dpi - up to 356 mm/sec - USB 2.0 - LAN - serial - USB host - Bluetooth 4.1 - cutter

Group	Printers
Manufacturer	Zebra
Manufacturer item no.	ZT41142-T0E0000Z
EAN/UPC	4062621268173



## Description

Keep your critical operations running efficiently with Zebra's durable ZT400 Series printer, designed for years of performance in a wide array of applications.

The ZT400 Series builds on the field-proven reliability of the Z Series with advancements in print speed, print quality and connectivity options. Designed for ease of use, the ZT400 Series printers offer an intuitive iconbased LCD graphical user interface and easy supplies loading. And, they include standard USB, Serial, Ethernet and Bluetooth capabilities. Expanded RFID capacities deliver greater tracking abilities, deeper visibility and enterprise insights.

Designed to grow with your evolving business needs. The ZT400 features increased processing capabilities and an open operating architecture providing flexibility to support your ever-growing and changing application requirements.

## Main features

Product Description	Zebra ZT400 Series ZT411 - label printer - B/W - direct thermal / thermal transfer
Printer Type	Label printer - direct thermal / thermal transfer - B/W
Weight	16.33 kg
Localisation	United Kingdom, Europe
Max Media Size	Roll (11.4 cm)
Min Media Size (Custom)	25.4 mm
Max Media Size (Custom)	114 mm
Print Speed	Up to 356 mm/sec - max speed
Max Resolution (B&W)	203 dpi
Cutter	Yes
Interface	USB 2.0, LAN, serial, USB host, Bluetooth 4.1
RAM Installed (Max)	256 MB
Flash Memory Installed (Max)	512 MB
Language Simulation	ZPL, ZPL II, EZPL, ZBI 2.0
Barcodes	Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 11, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, PLANET, TLC39, Plessey, Code 128B, Code 128C, Code 128A, Standard 2 of 5
Media Type	Continuous labels, die cut labels
Features	Realtime clock, transmissive media sensor, reflective media sensor
Networking	Print server

Power	AC 120/230 V
Dimensions (WxDxH)	26.9 cm x 49.5 cm x 32.4 cm

## Extended details

### General

Printer Type	Label printer - direct thermal / thermal transfer - monochrome
Localisation	United Kingdom, Europe

### Printer

Print Speed	Up to 356 mm/sec - max speed
Built-in Devices	4.3 inch LCD touch screen
Connectivity Technology	Wireless
Interface	USB 2.0, LAN, serial, USB host, Bluetooth 4.1
Max Resolution (B&W)	203 dpi
Language Simulation	ZPL, ZPL II, EZPL, ZBI 2.0
Features	Realtime clock, transmissive media sensor, reflective media sensor
Cutter	Yes
Fonts Included	16 x bitmapped   2 x scalable
Barcodes	Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 11, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, PLANET, TLC39, Plessey, Code 128B, Code 128C, Code 128A, Standard 2 of 5

### RAM

RAM Installed (Max)	256 MB
---------------------	--------

### Flash Memory

Flash Memory	512 MB
--------------	--------

### Media Handling

Media Type	Continuous labels, die cut labels
Max Media Size	Roll (11.4 cm)
Min Media Size (Custom)	25.4 mm
Max Media Size (Custom)	114 mm
Media Sizes	Roll (2.54 - 11.4 cm)
Max Printing Width	104 mm
Max Printing Length	3988 mm
Media Thickness Range	0.058 mm - 0.25 mm
Roll Maximum Outer Diameter	203 mm
Roll Core Diameter	76 mm
Media Feeders	1 x manual - 1 roll - Roll (11.4 cm)

### Networking

Networking	Print server
------------	--------------

### Expansion / Connectivity

Connections	1 x RS-232   1 x USB 2.0 - 4 pin USB Type B   1 x LAN - RJ-45   2 x USB host - 4 pin USB Type A
<b>Miscellaneous</b>	
Compliant Standards	FCC Class B certified, VCCI, C-Tick, BSMI, EN 61000-3-2, ICES-003, NOM, SABS, IEC 60950, EN 61000-3-3, EN55024, EN55022 Class B, CCC, KCC, S Mark, cTUVus, MFI
<b>Power</b>	
Power Device	Power supply - internal
Voltage Required	AC 120/230 V
Frequency Required	50/60 Hz
Power Factor Correction	Yes
<b>Environmental Standards</b>	
ENERGY STAR	Yes
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - parts and labour - 1 year
<b>Environmental Parameters</b>	
Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 85% (non-condensing)
<b>Dimensions &amp; Weight</b>	
Width	26.9 cm
Depth	49.5 cm
Height	32.4 cm
Weight	16.33 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.